

**2024**

# HUSQVARNA PRODUCTS AND SOLUTIONS

## CHAINSAWS

**125**

Cylinder displacement - 40 CC  
Rated power - 1.52 kW / 2hp @ 9000 rpm  
Weight (excl. cutting equipment) - 4.6 Kg

**135 MARK II**

Cylinder displacement - 38 CC  
Rated power - 1.6 kW / 2.1 hp @ 9000 rpm  
Weight (excl. cutting equipment) - 4.7 Kg  
X-TORQ®

**T435**

Cylinder displacement - 35.2 CC  
Rated power - 1.5 kW / 2 hp @ 10000 rpm  
Weight (excl. cutting equipment) - 3.4 Kg  
X-TORQ®

**445E II**

Cylinder displacement - 45.7 CC  
Rated power - 2.1 kW / 2.8 hp @ 9000 rpm  
Weight (excl. cutting equipment) - 5.1 Kg  
X-TORQ®

**353**

Cylinder displacement - 51.7 CC  
Rated power - 2.4 kW / 3.2 hp @ 9000 rpm  
Weight (excl. cutting equipment) - 5 Kg

**455 RANCHER**

Cylinder displacement - 55.5 CC  
Rated power - 2.6 kW / 3.4 hp @ 9000 rpm  
Weight (excl. cutting equipment) - 6 Kg  
X-TORQ®

**365**

Cylinder displacement - 65.1 CC  
Rated power - 3.4 kW / 4.5 hp @ 9300 rpm  
Weight (excl. cutting equipment) - 6.4 Kg

**272XP**

Cylinder displacement - 72.2 CC  
Rated power - 3.6 kW / 4.8 hp @ 9300 rpm  
Weight (excl. cutting equipment) - 6.3 Kg

**372XP**

Cylinder displacement - 70.7 CC  
Rated power - 3.9 kW / 5.3 hp @ 9600 rpm  
Weight (excl. cutting equipment) - 6.3 Kg

**390XP**

Cylinder displacement - 88 CC  
Rated power - 4.8 kW / 6.4 hp @ 9600 rpm  
Weight (excl. cutting equipment) - 7.3 Kg

**585****NEW**

Cylinder displacement - 86 CC  
Rated power - 5.1 kW / 6.83 hp @ 9600 rpm  
Weight (excl. cutting equipment) - 7.5 kg


**3120XP**

Cylinder displacement - 118.8 CC  
Rated power - 6.2 kW / 8.3 hp @ 9000 rpm  
Weight (excl. cutting equipment) - 10.4 Kg

## ACCESSORIES



X-Tough Bar



X-Force Bar



File Kit



LS 2T Oil



HP 2T Oil



Chain Oil



X-Cut Chains



Gloves Functional



Combi Can



Protective Boots



Helmet Classic CPL



Protective Glasses



Functional Chaps L



Hearing Protection

## POLESAW

**525PT5S**

Cylinder displacement - 25.4 CC  
Rated power - 1 kW / 1.3 hp @ 8500 rpm  
Length extended (including cutting equipment) - 402 cm

## POWER WEEDERS

### TF 120P

Rated power - 1.4 kW / 1.87 hp @ 3150 rpm  
Working width / depth - 460 mm / 150 mm  
Weight - 27 Kg  
Petrol powered



### TF 230

Rated power - 3.45 kW / 4.6 hp @ 3100 rpm  
Working width / depth - 750 mm / 300 mm  
Weight - 67 Kg  
Petrol powered  
Can fit attachments 4, 5, 6, 8 & 15



### TF 338P

NEW

Rated Power - 3.8 kW / 5.1 hp @ 3400 rpm  
Working width / depth - 950 mm / 300 mm  
Weight - 73 Kg  
Petrol powered  
Can fit 4, 5, 6, 8 & 15



### TF 545P

Rated power - 5 kW / 6.7 hp @ 3600 rpm  
Working width / depth - 1100 mm / 300 mm  
Weight - 113 Kg  
Petrol powered  
PTO  
Can fit all attachments



### TF 544+

Rated power - 5.8 kW / 7.8 hp @ 3300 rpm  
Working width / depth - 1350 mm / 300 mm  
Weight - 151 Kg  
Diesel powered  
Can fit attachments 3, 4, 5, 6, 7, 8, 9, 10, 13 & 15



### TF 545D+

Rated power - 5.8 kW / 7.8 hp @ 3300 rpm  
Working width / depth - 1350 mm / 300 mm  
Weight - 164 Kg  
Diesel powered  
PTO  
Can fit all attachments



### TF 545DE+

Rated power - 5.8 kW / 7.8 hp @ 3300 rpm  
Working width / depth - 1350 mm / 300 mm  
Weight - 167 Kg  
Diesel powered  
PTO  
Self start  
Can fit all attachments



## ATTACHMENTS

A - TYPE ROTARY CULTIVATOR



1

B - TYPE DITCHER



2

DEEP HOE KIT



3

DITCHING BLADE



4

PLOUGH



5

POTATO PLOUGH



6

ANTIWIND BLADE KIT



7

WHEEL KIT



8

PADDY WHEEL KIT



9

RIDGER



10

3" WATER PUMPS



11

SWATHER



12

METAL WHEEL KIT



13

SPRAYER



14

CONNECTING BRACKET



15

## WATER PUMPS

### W25P (1")



Cylinder Displacement - 25.4 CC  
Total head - 32 m  
Maximum delivery - 110 LPM  
Petrol powered  
2 Stroke

### W40P (1.5")



Cylinder Displacement - 97 CC  
Total head - 15 m  
Maximum delivery - 200 LPM  
Petrol powered  
4 Stroke  
CE Certification

### W50P (2")



Cylinder Displacement - 196 CC  
Total head - 30 m  
Maximum delivery - 533 LPM  
Petrol powered  
4 Stroke  
CE Certification

### W80P (3")



Cylinder Displacement - 196 CC  
Total head - 28 m  
Maximum delivery - 900 LPM  
Petrol powered  
4 Stroke  
CE Certification



## BRUSHCUTTERS

### 321R



Cylinder displacement - 25.4 CC  
Rated power - 0.75kW / 0.9 hp @ 8000 rpm  
Weight (excl. cutting equipment) - 6.1 Kg

### 131R



Cylinder displacement - 32.6 CC  
Rated power - 0.9 kW / 1.2 hp @ 7000 rpm  
Weight (excl. cutting equipment) - 7 Kg

### 331R



Cylinder displacement - 32.6 CC  
Rated power - 1 kW / 1.3 hp @ 7000 rpm  
Weight (excl. cutting equipment) - 7.2 Kg

## ACCESSORIES



## CLEARING BRUSHCUTTER

### 531RS

NEW



Cylinder displacement - 33.6 CC  
Rated power - 1.2 kW / 1.6 hp @ 7500 rpm  
Weight (excl. cutting equipment) - 7.1 Kg

### 541RS

NEW



Cylinder displacement - 41.5 CC  
Rated power - 1.6 kW / 2.1 hp @ 7500 rpm  
Weight (excl. cutting equipment) - 7.3 Kg

### 545FR



Cylinder displacement - 45.7 CC  
Rated power - 2.1 kW / 2.8 hp @ 9000 rpm  
Weight (excl. cutting equipment) - 8.7 Kg  
X-TORQ®

## EARTH AUGER

### 541EA

NEW



Cylinder displacement - 41.5 CC  
Engine Power - 1.47 kW / 1.97 hp  
Weight - 9.7 kg  
Drill bit diameter (mm) - 80,150, 200,250  
Extension rod available (mm) - 600,1000

## BACKPACK BRUSHCUTTERS

### 131RB



Cylinder displacement - 32.6 CC  
Rated power - 0.9 kW / 1.2 hp @ 7000 rpm  
Weight (excl. cutting equipment) - 10.2 Kg

### 331RB



Cylinder displacement - 32.6 CC  
Rated power - 1 kW / 1.3 hp @ 7000 rpm  
Weight (excl. cutting equipment) - 9.9 Kg

### 531RB

NEW



Cylinder displacement - 33.6 CC  
Rated power - 1.1 kW / 1.48 hp @ 7500 rpm  
Weight (excl. cutting equipment) - 8.9 kg

### 541RB

NEW



Cylinder displacement - 41.5 CC  
Rated power - 1.47 kW / 1.97 hp @ 7500 rpm  
Weight (excl. cutting equipment) - 9 Kg

## MULTI PURPOSE ENGINES

### HH 163MP



Cylinder Displacement - 163 CC  
Output shaft - parallel ¾ inch  
Rated power - 4.1 kW / 5.5 hp @ 3600 rpm

### HH 196MP



Cylinder Displacement - 196 CC  
Output shaft - parallel ¾ inch  
Rated power - 4.8 kW / 6.5 hp @ 3600 rpm

### HH 270MP



Cylinder Displacement - 270 CC  
Output shaft - parallel 1 inch  
Rated power - 6.7 kW / 9 hp @ 3600 rpm

### HH 389MP



Cylinder Displacement - 389 CC  
Output shaft - parallel 1 inch  
Rated power - 9.6 kW / 13 hp @ 3600 rpm

## OUTBOARD ENGINE

### HH 2120B



Cylinder Displacement - 212 CC  
Output Shaft - parallel ¾ inch  
Rated power - 5.6 kW / 7.5 hp @ 4600 rpm

## BACKPACK SPRAYERS

### 321S15 & 321S25



Tank Capacity - 15 L & 25 L  
Rated power - 0.7 kW / 0.9 hp @ 7000 rpm  
Weight - 9.2 Kg / 10 Kg

## MISTER

### 362M18



Rated Power - 2.8 kW/3.75 hp @ 7500 rpm  
Weight - 12 Kg  
Coverage Vertical / Horizontal - 12 / 12 M

## DUSTER

### 362D28



Rated power - 2.8 kW/3.75 hp @ 7500 rpm  
Weight - 12 Kg  
Coverage Vertical / Horizontal - 22 / 12 M  
Mister Conversion Kit Available for Duster

## PORTABLE SPRAYER

### 321SP



Working pressure - 15 - 35 Bar  
Rated power - 0.7 kW / 0.9 hp @ 7000 rpm  
Max Working Flowrate - 4 LPM

## MANUAL SPRAYERS

### 301 SM

NEW



Tank capacity - 1.5 L  
Working pressure - 0 to 3bar  
Spray volume - 300 ml/min  
Weight - 0.53 kg

### 308 SM

NEW



Tank capacity - 8 L  
Working pressure - 3 bar  
Spray volume - 800 ml/min  
Weight - 1.8 kg

### 320 SM

NEW



Tank capacity - 20 L  
Working pressure - 3 bar  
Spray volume - 800 ml/min  
Weight - 3.4 kg

## TRACTORS

### TC 114

NEW



Rated power - 9 kW / 12.06 hp @ 2800 rpm  
Cutting width - 95 cm / 37.4 inches  
Cutting height - 25 to 100 mm / 0.98 - 3.93 inches  
Collector capacity - 250 L  
Powered by Husqvarna Engine

### TS 114

NEW



Rated power - 9 kW / 12.06 hp @ 2800 rpm  
Cutting width - 95 cm / 37.4 inches  
Cutting height - 25 to 100 mm / 0.98 - 3.93 inches  
Powered by Husqvarna Engine

## RIDER

### R213C



Rated power - 6.6 kW / 8.8 hp @ 3000 rpm  
Cutting width - 940 mm / 37 inches  
Cutting height - 25 to 75 mm / 0.98 - 2.9 inches

### LC118 (PUSH TYPE)



Rated power - 2.2 kW / 2.9 hp @ 2900 rpm  
Cutting width - 460 mm / 18 inches  
Cutting height - 16 to 80 mm / 0.6 - 3.1 inches  
Powered by Husqvarna Engine

### LC141C (PUSH TYPE)



Motor power - 1800 W  
Cutting width - 410 mm / 16.14 inches  
Cutting height - 25 - 75 mm / 0.98 - 2.95 inches  
Electric Corded

### LC419SP (SELF PROPELLED)



Rated power - 2.75 kW / 3.68 hp @ 2900 rpm  
Cutting width - 480 mm / 18.8 inches  
Cutting height - 15 to 75 mm / 0.59 - 2.95 inches  
Powered by Husqvarna Engine

## PRESSURE WASHERS

### PW 130



Max Pressure - 130 Bar  
Water flow - 324 - 465 l/hr  
Motor power - 1500 W

### PW 240



Max Pressure - 140 Bar  
Water flow - 348 - 465 l/hr  
Motor power - 1800 W

### PW350



Max pressure - 150 bar  
Water flow - 420 - 500 l/hr  
Motor power - 2100 W

### PW480



Max pressure - 180 bar  
Water flow - 540 - 610 l/hr  
Motor power - 2900 W

## BLOWERS

### 125B

NEW



Blowing force - 12.5 N  
Air speed (Flat nozzle) - 76 m/s  
Air flow (In housing) - 13.3 m³ / min  
Rated power - 0.8kW / 1 hp @ 8000 rpm

### 525BX



Blowing force - 15 N  
Air speed (Flat Nozzle) - 86 m/s  
Air flow (in housing) - 14 m³/min  
Rated power - 0.81 kW / 1.08 hp @ 7300 rpm  
X-TORQ®

### 345BT

NEW



Blowing force - 22 N  
Air speed (Round Nozzle) - 120.7 m/s  
Air flow (In housing) - 21.6 m³ / min  
Rated power - 1.6kW / 2.14 hp @ 7000 rpm

### 570BTS



Blowing force - 37 N  
Air speed (Round Nozzle) - 106 m/s  
Air flow (in housing) - 28 m³ / min  
Rated power - 2.9kW / 3.88 hp @ 8000 rpm  
X-TORQ®

## HEDGE TRIMMERS

### 578BTF



Blowing force - 33 N  
Air speed (round nozzle) - 100 m/s  
Air flow (in housing) - 25 m³/min  
Rated power - 3.14 kW / 4.21 hp @ 8000 rpm  
X-TORQ®

### 122HD45



Cylinder displacement - 21.7 CC  
Rated power - 0.6 kW / 0.8 hp @ 7800 rpm  
Knife length : 450 mm  
Weight - 4.6 Kg

### 522HD60S

NEW



Cylinder displacement - 21.7 CC  
Rated power - 0.6 kW / 0.8 hp @ 7800 rpm  
Knife Length : 600 mm  
Weight - 5 Kg  
Adjustable Rear Handle



**AUTHORISED DEALER:**

**Husqvarna (India) Products Private Limited**

1st Floor, Swelect House, No. 5, Sir PS Sivasamy Salai, Mylapore,  
Chennai - 600004, Tamil Nadu, India  
Email: support.in@husqvarnagroup.com